



THE ALU-REX PRODUCT LINES

AT A GLANCE

FOR NEW RAIN GUTTERS SURROUNDED BY A LOT OF TREES

DoublePro® is a patented dual-action gutter protection system. This continuous hanger™ with built-in guard is designed to stand up to the worst weather conditions in North America and keep your gutter free of debris and ice year after year.


FOR NEW RAIN GUTTERS SURROUNDED BY LITTLE OR NO TREES

T-Rex® is also a continuous fastening system for gutters. It mounts rain gutters solidly on houses, making them much sturdier and longer-lasting than those mounted with spikes and hangers spaced at intervals.

Hover[™] is the improved continuous fastening system that allows to suspend gutters instead of screwing them through using the patented Floating[™] technology. It is compatible with hemmed back gutters.

FOR EXISTING RAIN GUTTERS

Gutter Clean[®] is installed over existing rain gutters, without replacing them keeping leaves and debris from getting into and clogging the gutters.



double **& pro**® t *** rex**®

hover**™ gutterclean**№











FOR NEW GUTTERS SURROUNDED BY A LOT OF TREES	✓			
FOR NEW GUTTERS SURROUNDED BY LITTLE OR NO TREES	 	J	√	
COMPATIBLE WITH floating TECHNOLOGY AND HEMMED BACK GUTTERS	V		V	
INSTALL OVER EXISTING RAIN GUTTERS				√
Support at least 250 lb per linear foot	V	√	√	
Replace spikes and hangers as gutter fasteners	V	√	V	
Assemble with the gutter on the ground	V	√	V	
Protect gutters from pine needles	V			
Protect gutters from leaves and debris	V	√	V	√
Can handle at least 29.7" of water per hour	V	√	V	✓
Reduce problems with ice and snow	V	√	V	✓
Warranty on material	LIFETIME	LIFETIME	LIFETIME	25 YEARS
Warranty on sturdiness	LIFETIME	LIFETIME	LIFETIME	
Clog-free warranty against leaves	LIFETIME	25 YEARS PRORATED	25 YEARS PRORATED	25 YEARS PRORATED
Clog-free warranty against pine needles	LIFETIME			


CONTINUOUS HANGERS": EXPLAINED



Rain gutters are commonly installed with spaced hangers that cause weak spots on the gutter between each hanger.



To avoid weak spots, hundreds of hangers would need to be added, but this is not a very efficient practice.



With a **continuous hanger™**, the rain gutters are reinforced along their entire length.



Rain gutters flow freely for perfect drainage year-round.

SEE THE **BENEFITS**

Acts as uv shade protecting the sealant from direct sunlight and eliminating corner leaks.

Keeps leaves and debris out of rain gutters.

double **& pro**®

CONTINUOUS HANGER™ WITH BUILT-IN GUTTER GUARD



- Protects against clogs caused by leaves and pine needles
- > Replaces spikes and hangers
- > Strengthens the gutter
- · Available for 5" and 6" gutters
- Available for Floating[™] technology and hemmed back gutters




eclipse™ TECHNOLOGY



vortex™ TECHNOLOGY





The offset holes of the **eclipse** TECHNOLOGY make it the perfect filter, allowing water to drain freely while blocking pine needles and leaves without ever getting clogged.

With the **vortex** TECHNOLOGY, the suction created by the two membranes makes it possible to drain three times more water than recorded in the heaviest storms.

D-11500 (5" BLACK)

Aluminum Carbon Black and Clear backer 200 screws included 12 end trims included Length: 7.5' Top layer thickness: 0.017"

Bottom layer thickness: 0.014"

24 pcs per ctn 180' per ctn Ctn: 90" x 11" x 5" 47 lb 24 ctns per skid (4,320') Skid: 7.5' x 4' 1,200 lb

D-11600 (6" BLACK)

Aluminum Carbon Black and Clear backer 200 screws included 12 end trims included Length: 7.5' Top layer thickness: 0.017" Bottom layer thickness: 0.014"

24 pcs per ctn 180' per ctn Ctn: 90" x 14" x 5" 56 lb 21 ctns per skid (3,780') Skid: 7.5' x 4' 1,229 lb

DF-11500 (5" BLACK) () floating TECHNOLOGY



Aluminum

Carbon Black and Clear backer

200 screws included 12 end trims included

Length: 7.5'

Top layer thickness: 0.017" Bottom layer thickness: 0.014"

24 pcs per ctn 180' per ctn Ctn: 90" x 11" x 5" 47 lb

24 ctns per skid (4,320') Skid: 7.5' x 4' 1,200 lb



DF-11600 (6" BLACK) (Ŋ) floating™ TECHNOLOGY



Aluminum Carbon Black and Clear backer 200 screws included 12 end trims included

Length: 7.5'

Top layer thickness: 0.017" Bottom layer thickness: 0.014"

24 pcs per ctn 180' per ctn Ctn: 90" x 14" x 5" 56 lb 21 ctns per skid (3,780') Skid: 7.5' x 4' 1,229 lb



ACCESSORIES



END TRIMS

- > Aluminum + FlexSeal™
- > Carbon Black
- > 12 trims per bag
- TR-500 (5")
- TR-600 (6")



SCREWS

- > Black head hex 1/4"
- > Rubber Washer
- > Zinc Dacrotized®
- > Bag of 100 screws # 10 1-1/2 screw
- SKU: SCREW1011/2BK (BLACK)



CUT-FREE UNIVERSAL CORNERS

- > Aluminum
- > Carbon Black
- > Top layer thickness: 0.017"
- > Bottom layer thickness: 0.014"
- > 10 corners
- · UCF-11500 (5")
- UCF-11600 (6")



UNIVERSAL ACCESSORY

- > Aluminum
- > Carbon Black
- > Top layer thickness: 0.017"
- > Bottom layer thickness: 0.014"
- > 10 corners or 20 access panels
- · UA-11500 (5")
- UA-11600 (6")



CONTINUOUS HANGER™

FOR RAIN GUTTERS





Unparalleled Strength





With t*rex; your rain gutters are reinforced from end to end. There are no weak points. It can even hold the weight of three people.

Higher UV-ray filtration extends the elastic properties of the gutter sealant and reduces drying, cracking and leakage at each corner of the rainwater management system.

M-5200 B95 (5" BLACK)

PRODUCT

Aluminum Carbon Black backer 300 screws included Length: 7.5' Thickness: 0.017"



48 pcs per ctn 360' per ctn Ctn: 90" x 11" x 8" 56 lb 20 ctns per skid (7,200') Skid: 7.5' x 4' 1,120 lb

M-5200 (5" MILL)

Aluminum

Gold backer

Length: 7.5'

300 screws included

Ctn: 90" x 11" x 8" 56 lb

20 ctns per skid (7,200')

Skid: 7.5' x 4' 1,120 lb

Thickness: 0.017"

48 pcs per ctn

360' per ctn

M-6200 B95 (6" BLACK)

PRODUCT

Aluminum Carbon Black backer 300 screws included Length: 7.5' Thickness: 0.017"

34 pcs per ctn



255' per ctn Ctn: 90" x 13" x 6" 48 lb 24 ctns per skid (6,120') Skid: 7.5' x 4' 1,152 lb

M-6200 (6" MILL)

PRODUCT

Aluminum Gold backer 300 screws included Length: 7.5' Thickness: 0.017"



34 pcs per ctn 255' per ctn Ctn: 90" x 13" x 6" 48 lb 24 ctns per skid (6,120') Skid: 7.5' x 4' 1,152 lb

M-7200 (7" MILL) - Special order*

PRODUCT

Aluminum Gold backer 200 screws included Length: 7.5' Thickness: 0.021"



24 pcs per ctn 180' per ctn Ctn: 90" x 13" x 8" 50 lb 20 ctns per skid (3,600') Skid: 7.5' x 4' 1,000 lb

*Minimum order of 1 skid. Ask your Alu-Rex account manager or your distributor for more information.

0

ACCESSORIES



CORNERS

- > Aluminum
- > Carbon Black or Mill finish
- > Thickness: 0.017"
- > 20 pieces per ctn

Inside

- IC-5200D B95 (5" BLACK)
- IC-6200D B95 (6" BLACK)
- IC-5200D (5" MILL)
- IC-6200D (6" MILL)
- Includes 10 water diverters

Outside

- OC-5200D B95 (5" BLACK)
- OC-6200D B95 (6" BLACK)
- OC-5200D (5" MILL)
- OC-6200D (6" MILL)



ACCESS PANELS

- > Easy way to access the gutter
- > 20 pieces per ctn
- AP-5200 B95 (5" BLACK)
- AP-6200 B95 (6" BLACK)
- AP-5200 (5" MILL)
- AP-6200 (6" MILL)



WATER DIVERTERS

- > Included in inside corner boxes or 30 pieces per ctn
- > Thickness: 0.017"
- For M-5200 B95 (BLACK)
- For M-5200 (WHITE)



SCREWS

- > Black or mill head hex 1/4"
- > Rubber Washer
- > Zinc Dacrotized®
- > Bag of 100 screws # 10 1-1/2 screw
- SKU: SCREW1011/2BK (BLACK)
- SKU: SCREW1011/2 (MILL)



BITS

- > 6" long
- > Head hex 1/4"
- > Magnetic



CONTINUOUS HANGER™

FOR FLOATING & HEMMED BACK GUTTERS





floating™ TECHNOLOGY



spring **W** back™ TECHNOLOGY





With the **floating** TECHNOLOGY, gutters can be suspended from the building fascia without even puncturing them. As a result, they maintain their freedom to change shape without expansion joint.


The spring \mathemathtarrow back TECHNOLOGY will prevent gutter distortion under a weight of over 400 lb per linear foot, by distributing the pressure along the entire length of the Hover continuous hanger.

H-5000 (5" BLACK)

floating™ TECHNOLOGY

Aluminum Carbon Black backer 300 screws included 12 end trims included Length: 7.5' Thickness: 0.017"

48 pcs per ctn 360' per ctn Ctn: 90" x 14" x 7" 56 lb 18 ctns per skid (6,480') Skid: 7.5' x 4' 1,282 lb



H-6000 (6" BLACK) (n

floating™ TECHNOLOGY

Aluminum Carbon Black backer 300 screws included 12 end trims included Length: 7.5' Thickness: 0.017"

34 pcs per ctn 255' per ctn Ctn: 90" x 13" x 6" 54 lb 21 ctns per skid (5,355') Skid: 7.5' x 4' 1,246 lb




ACCESSORIES



UNIVERSAL CORNERS AND ACCESS PANELS (3 IN 1)

- > Aluminum
- > Carbon Black
- > Thickness: 0.017"
- > 15 corners or 30 panels per ctn
- UA-5000 (5")
- UA-6000 (6")



END TRIMS

- > Aluminum + FlexSeal™
- > Carbon Black
- > 12 trims per bag
- TR-500 (5")
- TR-600 (6")



SCREWS

- > Black head hex 1/4"
- > Rubber Washer
- > Zinc Dacrotized®
- > Bag of 100 screws # 10 1-1/2 screw
- SKU: SCREW1011/2BK (BLACK)

gutter*clean


RAIN GUTTER PROTECTION





flex a seal TECHNOLOGY





The flex **a seal** TECHNOLOGY is made of materials resistant to UV rays, mold and temperature variations ensuring that the back of the gutter is watertight.

The alu*perf" TECHNOLOGY is optimized perforations size create the perfect combination of maximum drainage and minimum debris. It drains 29.7" (754 mm) of water per hour.

M-5300 (5" MILL)

Aluminum Gold backer Length: 7.44' Thickness: 0.017"

PACKAGING

43 pcs per ctn 320' per ctn Ctn: 90" x 12" x 5" 42 lb 24 ctns per skid (7,680') Skid: 7.5' x 4' 1,008 lb

M-6300 (6" MILL)

PRODUCT

Aluminum Gold backer Length: 7.44' Thickness: 0.017"

ACKAGING

43 pcs per ctn 320' per ctn Ctn: 90" x 13" x 6" 52 lb 21 ctns per skid (6,720') Skid: 7.5' x 4' 1,092 lb

M-53ZIP (5" MILL)

RODUCT

Aluminum Gold backer Length: 7.44' Thickness: 0.017"

ACKAGING

43 pcs per ctn 320' per ctn Ctn: 90" x 12" x 6" 52 lb 21 ctns per skid (6,720') Skid: 7.5' x 4' 1.092 lb

M-63ZIP (6" MILL)

RODUCT

Aluminum Gold backer Length: 7.44' Thickness: 0.017"

PACKAGING

43 pcs per ctn 320' per ctn Ctn: 90" x 13" x 6" 54 lb 21 ctns per skid (6,720') Skid: 7.5' x 4' 1,134 lb

MC-5100 (5" COPPER)

RODUCT

Copper 100 screws included Length: 7.5' Thickness: 0.017"

ACKAGING

16 pcs per ctn 120' per ctn Ctn: 90" x 7" x 3" 51 lb 35 ctns per skid (4,200') Skid: 7.5' x 4' 1,785 lb

M-5300 B95 (5" BLACK)

PRODUCT

Aluminum Carbon Black backer Length: 7.44' Thickness: 0.017"

CKAGING

43 pcs per ctn 320' per ctn Ctn: 90" x 12" x 5" 42 lb 24 ctns per skid (7,680') Skid: 7.5' x 4' 1,008 lb

M-6300 B95 (6" BLACK)

RODUCT

Aluminum Carbon Black backer Length: 7.44' Thickness: 0.017"



43 pcs per ctn 320' per ctn Ctn: 90" x 13" x 6" 52 lb 21 ctns per skid (6,720') Skid: 7.5' x 4' 1,092 lb

M-53ZIP B95 (5" BLACK)



Aluminum Carbon Black backer Length: 7.44' Thickness: 0.017"

43 pcs per ctn



320' per ctn Ctn: 90" x 12" x 6" 52 lb 21 ctns per skid (6,720') Skid: 7.5' x 4' 1,092 lb

M-63ZIP B95 (6" BLACK)

RODUCT

Aluminum Carbon Black backer Length: 7.44' Thickness: 0.017"



43 pcs per ctn 320' per ctn Ctn: 90" x 13" x 6" 54 lb 21 ctns per skid (6,720') Skid: 7.5' x 4' 1,134 lb

MC-6100 (6" COPPER)

RODUCT

Copper 100 screws included Length: 7.5' Thickness: 0.017"



16 pcs per ctn 120' per ctn Ctn: 90" x 7" x 3" 68 lb 35 ctns per skid (4,200') Skid: 7.5' x 4' 2,380 lb

RAIN GUTTER PROTECTIONFOR HALF ROUND GUTTER



TO ORDER

HR-5400 (5" ALU - INSIDE BEAD)

PRODUCT

Aluminum Gold backer Length: 7.5' Thickness: 0.0215"

16 pcs per ctn

PACKAGING

120' per ctn Ctn: 90.25" x 7.75" x 2.25" 22 lb 40 ctns per skid (4,800') Skid: 7.67' x 3.75' 880 lb

HR-6400 (6" ALU - INSIDE BEAD)

RODUCT

Aluminum Gold backer Length: 7.5' Thickness: 0.0215"

CKAGING

16 pcs per ctn 120' per ctn Ctn: 90.25" x 7.75" x 2.25" 25 lb 40 ctns per skid (4,800') Skid: 7.67' x 3.75' 1,000 lb

HR-333-D (6" ALU - OUTSIDE BEAD)

PRODUCT

Aluminum Clear backer 44 Stainless steel clips included 40 Stainless steel supports included Length: 7.5' Thickness: 0.0215"

ACKAGING

16 pcs per ctn 120' per ctn Ctn: 90.25" x 7.75" x 2.25" 22 lb 40 ctns per skid (4,800') Skid: 7.67' x 3.75' 880 lb



HRC-5400 (5" COPPER - INSIDE BEAD)

PRODUCT

Copper 100 screws included Length: 7.5' Thickness: 0.016"

ACKAGING

16 pcs per ctn 120' per ctn Ctn: 90.25" x 7.75" x 2.25" 49 lb 24 ctns per skid (2,880') Skid: 7.67' x 3.75' 1,176 lb

HRC-6400 (6" COPPER - INSIDE BEAD)

PRODUCT

Copper 100 screws included Length: 7.5' Thickness: 0.016"



16 pcs per ctn 120' per ctn Ctn: 90.25" x 7.75" x 2.25" 57 lb 24 ctns per skid (2,880') Skid: 7.67' x 3.75' 1,368 lb

COMPATIBILITY

Multiple profiles of half-round gutters are available on the market. Make sure your style of gutter matches our product specifications.

FOR SPECIFICATION SHEETS, INSTALLATION GUIDES AND WARRANTY SHEETS:



ALU-REX.COM/TECH



FOR MORE INFORMATION

1.855.525.8739 — CONTACT@ALU-REX.COM



SOME PRODUCTS IN THIS GUIDE MAY BE COVERED BY ONE OR MULTIPLE PATENTS.

WWW.ALU-REX.COM • 1.855.525.8739

V.2023/04/USA